

* Warequip accepts no responsibility for equipment that is operated incorrectly, or not in accordance with operation manuals.

Zallys M12



TOW CAPACITY – 1000kg on a level concrete surface

Evenly distributed loads as recommended

DO NOT OVERLOAD or obstruct operator view with high loads.

OPERATION

The unit is designed to trail behind the user. The front of the unit is the tiller head end.

POWER – ON/OFF SWITCH

The Key switch is located on the right hand side of the tiller post, turn the Key switch to on position for normal operation. If powered status light flashes there may be a fault, please contact your supplier.



BATTERY INDICATOR

When fully charged the lights will illuminate to show 100%, as you use the tug the lights will change to show the level. Once the charges falls to 40% we recommend charging, a red light will flash for approximately 10 minutes before the unit loses all charge.



EMERGENCY STOP BACK OFF BUTTON

Stops and repels the unit if activated when reversing.



HORN

To activate the horn, press and hold this button. Release the button to stop horn.



PADDLE LEVER

When facing the machine; (Forward motion is to the tiller end)

Push lever down for forward motion.

Push lever forward for reverse motion.

The speed is determined by how far you turn the paddle.

The Tug and load should follow behind you when walking.



Zallys M12



TILLER HEAD ADJUSTMENT

To adjust the tiller head up and down use the piston release lever, adjust the tiller to the required height to suit you.



M12 BODY ADJUSTMENT

To adjust the angle of the body use the lower piston release lever, adjust to the required angle. Please ensure the angle suits the load to be towed to keep the unit stable.



CHARGING

Unit has an external charger which is supplied separately to the machine

The charging point is located on the lower panel on the front of the unit. Disconnect by pulling the two plugs apart.

Plug the charger lead into the plug on the tug (the plug will only fit the correct end) and then into a 240V 10amp power point. – Charge with key switch in the OFF POSITION.

Turn the switch on at the power point, the lights will come on and flash for approximately 30 seconds then the charge will begin. The charge is complete once a green light is shown on the charger.

If a flashing light appears please contact your supplier.

OVERNIGHT CHARGE IS RECOMMENDED

ONLY USE THE CHARGER SUPPLIED WITH THE UNIT.



Hitching

Various hitches can be supplied with the unit to suit your application.

Always ensure connection takes place on a level surface.

Activate the brakes on the trolley. Approach the trolley at a slow speed, ensure the centre of the hitch is in line with the centre of the trolley.

Always ensure the trolley has made correct connection before unlocking the trolley brake and driving away.



Please ensure you are familiar with the manual and the correct operating instructions.

If in doubt contact supplier before use.